



Intel® Core™ i5-8500T Processor

9M Cache, up to 3.50 GHz

Specifications

[Export specifications](#)

Essentials

| | |
|----------------------------|---|
| Product Collection | 8th Generation Intel® Core™ i5 Processors |
| Code Name | Products formerly Coffee Lake |
| Vertical Segment | Desktop |
| Processor Number | i5-8500T |
| Status | Launched |
| Launch Date | Q2'18 |
| Lithography | 14 nm |
| Recommended Customer Price | \$192.00 |
| Use Conditions | Embedded Broad Market Commercial Temp, PC/Client/Tablet |

Performance

| | |
|---------------------------------|-----------------|
| # of Cores | 6 |
| # of Threads | 6 |
| Processor Base Frequency | 2.10 GHz |
| Max Turbo Frequency | 3.50 GHz |
| Cache | 9 MB SmartCache |
| Bus Speed | 8 GT/s DMI3 |
| TDP | 35 W |
| Configurable TDP-down Frequency | 1.60 GHz |
| Configurable TDP-down | 25 W |

Supplemental Information

| | |
|----------------------------|--------------------------|
| Embedded Options Available | Yes |
| Datasheet | View now |

Memory Specifications

| | |
|--|-------|
| Max Memory Size (dependent on memory type) | 64 GB |
|--|-------|

| | |
|--------------------------|-----------|
| Memory Types | DDR4-2666 |
| Max # of Memory Channels | 2 |
| Max Memory Bandwidth | 41.6 GB/s |
| ECC Memory Supported ‡ | No |

Processor Graphics

| | |
|---|-------------------------|
| Processor Graphics ‡ | Intel® UHD Graphics 630 |
| Graphics Base Frequency | 350 MHz |
| Graphics Max Dynamic Frequency | 1.10 GHz |
| Graphics Video Max Memory | 64 GB |
| 4K Support | Yes, at 60Hz |
| Max Resolution (HDMI 1.4)‡ | 4096x2304@24Hz |
| Max Resolution (DP)‡ | 4096x2304@60Hz |
| Max Resolution (eDP - Integrated Flat Panel)‡ | 4096x2304@60Hz |
| DirectX* Support | 12 |
| OpenGL* Support | 4.5 |
| Intel® Quick Sync Video | Yes |
| Intel® InTru™ 3D Technology | Yes |
| Intel® Clear Video HD Technology | Yes |
| Intel® Clear Video Technology | Yes |
| # of Displays Supported ‡ | 3 |
| Device ID | 0x3E92 |

Expansion Options

| | |
|------------------------------|--------------------------|
| Scalability | 1S Only |
| PCI Express Revision | 3.0 |
| PCI Express Configurations ‡ | Up to 1x16, 2x8, 1x8+2x4 |
| Max # of PCI Express Lanes | 16 |

Package Specifications

| | |
|--------------------------------|-----------------|
| Sockets Supported | FCLGA1151 |
| Max CPU Configuration | 1 |
| Thermal Solution Specification | PCG 2015A (35W) |
| T _{JUNCTION} | 100°C |
| Package Size | 37.5mm x 37.5mm |
| Low Halogen Options Available | See MDDS |

Advanced Technologies

| | |
|--|---|
| Intel® Optane™ Memory Supported ‡ | Yes |
| Intel® Turbo Boost Technology ‡ | 2.0 |
| Intel® vPro™ Platform Eligibility ‡ | Yes |
| Intel® Hyper-Threading Technology ‡ | No |
| Intel® Virtualization Technology (VT-x) ‡ | Yes |
| Intel® Virtualization Technology for Directed I/O (VT-d) ‡ | Yes |
| Intel® VT-x with Extended Page Tables (EPT) ‡ | Yes |
| Intel® TSX-NI | Yes |
| Intel® 64 ‡ | Yes |
| Instruction Set | 64-bit |
| Instruction Set Extensions | Intel® SSE4.1, Intel® SSE4.2, Intel® AVX2 |
| Idle States | Yes |
| Enhanced Intel SpeedStep® Technology | Yes |
| Thermal Monitoring Technologies | Yes |
| Intel® Identity Protection Technology ‡ | Yes |
| Intel® Stable Image Platform Program (SIPP) | Yes |

Security & Reliability

| | |
|--|-----|
| Intel® AES New Instructions | Yes |
| Secure Key | Yes |
| Intel® Software Guard Extensions (Intel® SGX) | Yes |
| Intel® Memory Protection Extensions (Intel® MPX) | Yes |
| Intel® OS Guard | Yes |
| Intel® Trusted Execution Technology ‡ | Yes |
| Execute Disable Bit ‡ | Yes |
| Intel® Boot Guard | Yes |

Compatible Products

Product Images

Ordering and Compliance

Downloads and Software

All information provided is subject to change at any time, without notice. Intel may make changes to manufacturing life cycle, specifications, and product descriptions at any time, without notice. The information herein is provided "as-is" and Intel does not make any representations or warranties whatsoever regarding accuracy of the information, nor on the product features, availability, functionality, or compatibility of the products listed. Please contact system vendor for more information on specific products or systems.

Intel classifications are for informational purposes only and consist of Export Control Classification Numbers (ECCN) and Harmonized Tariff Schedule (HTS) numbers. Any use made of Intel classifications are without recourse to Intel and shall not be construed as a representation or warranty regarding the proper ECCN or HTS. Your company as an importer and/or exporter is responsible for determining the correct classification of your transaction.

Refer to Datasheet for formal definitions of product properties and features.

"Announced" SKUs are not yet available. Please refer to the Launch Date for market availability.

Some products can support AES New Instructions with a Processor Configuration update, in particular, i7-2630QM/i7-2635QM, i7-2670QM/i7-2675QM, i5-2430M/i5-2435M, i5-2410M/i5-2415M. Please contact OEM for the BIOS that includes the latest Processor configuration update.

‡ This feature may not be available on all computing systems. Please check with the system vendor to determine if your system delivers this feature, or reference the system specifications (motherboard, processor, chipset, power supply, HDD, graphics controller, memory, BIOS, drivers, virtual machine monitor-VMM, platform software, and/or operating system) for feature compatibility. Functionality, performance, and other benefits of this feature may vary depending on system configuration.

See <http://www.intel.com/content/www/us/en/architecture-and-technology/hyper-threading/hyper-threading-technology.html?wapkw=hyper+threading> for more information including details on which processors support Intel® HT Technology.

Max Turbo Frequency refers to the maximum single-core processor frequency that can be achieved with Intel® Turbo Boost Technology. See www.intel.com/technology/turboboost/ for more information.

The Recommended Customer Price ("RCP") is pricing guidance for Intel products. Prices are for direct Intel customers, typically represent 1,000-unit purchase quantities, and are subject to change without notice. Taxes and shipping, etc. not included. Prices may vary for other package types and shipment quantities, and special promotional arrangements may apply. If sold in bulk, price represents individual unit. Listing of these RCP does not constitute a formal pricing offer from Intel. Please work with your appropriate Intel representative to obtain a formal price quotation.

System and Maximum TDP is based on worst case scenarios. Actual TDP may be lower if not all I/Os for chipsets are used.

Low Halogen: Applies only to brominated and chlorinated flame retardants (BFRs/CFRs) and PVC in the final product. Intel components as well as purchased components on the finished assembly meet JS-709 requirements, and the PCB / substrate meet IEC 61249-2-21 requirements. The replacement of halogenated flame retardants and/or PVC may not be better for the environment.

For benchmarking data see <http://www.intel.com/performance>.

Intel processor numbers are not a measure of performance. Processor numbers differentiate features within each processor family, not across different processor families. See <http://www.intel.com/content/www/us/en/processors/processor-numbers.html> for details.

Processors that support 64-bit computing on Intel® architecture require an Intel 64 architecture-enabled BIOS.