

Restrição Definitiva por Estado

BR	UF	PNV	Km Inicial	Km Final	Pista 1						Pista 2					
					Altura	Largura Faixa de Rolamento	Largura Total	Peso	Raio de Giro	Comp.	Altura	Largura Faixa de Rolamento	Largura Total	Peso	Raio de Giro	Comp.
174	RR	174BRR1030	617,5	631,5		9,2										
174	RR	174BRR1040	631,5	647,6		8,2										
174	RR	174BRR0710	100,7	102,8		9,1										
174	RR	174BRR0855	281,7	288,7		10,0										
174	RR	174BRR0780	178,0	182,4		9,0										
174	RR	174BRR0675	30,5	42,0		9,0										
174	RR	174BRR0685	42,0	66,5		9,0										
174	RR	174BRR0870	304,7	305,8		8,3										
174	RR	174BRR0915	430,6	431,3		8,3										
174	RR	174BRR0850	269,0	281,7		12,0										
174	RR	174BRR0945	493,0	493,6		8,3										
174	RR	174BRR0980	531,2	541,0		9,2										
174	RR	174BRR0745	143,6	151,3		9,0										
174	RR	174BRR0695	73,0	75,6		9,0										
174	RR	174BRR0720	108,5	118,0		9,0										
174	RR	174BRR0785	182,4	194,1		9,0										
174	RR	174BRR0670	0,0	30,5		9,0										
174	RR	174BRR0835	261,2	262,9		9,0										
174	RR	174BRR0705	88,5	100,7		9,0										
174	RR	174BRR1010	604,8	609,9		8,2										
174	RR	174BRR1020	609,9	615,0		9,2										
174	RR	174BRR0800	211,8	213,6		9,0										
174	RR	174BRR0690	66,5	73,0		9,0										
174	RR	174BRR0985	541,0	544,0		9,2										
174	RR	174BRR0700	75,6	88,5		9,0										
174	RR	174BRR0770	173,4	177,3		9,0										
174	RR	174BRR0950	493,6	502,0	5,7						5,7					
174	RR	174BRR0755	153,1	157,9		9,0										
174	RR	174BRR0790	194,1	208,3		9,0										
174	RR	174BRR0740	137,7	143,6		9,0										
174	RR	174BRR1060	659,5	673,9		8,1										
174	RR	174BRR0845	265,5	269,0		10,0										
174	RR	174BRR1065	673,9	676,3		8,0										
174	RR	174BRR1000	561,9	582,8		8,3										
174	RR	174BRR0750	151,3	153,1		9,0										
174	RR	174BRR0965	507,1	511,6		8,3										
174	RR	174BRR0940	485,4	493,0	5,7											
174	RR	174BRR1090	710,3	715,7		9,5										
174	RR	174BRR0805	213,6	225,1		10,0										
174	RR	174BRR0735	123,2	137,7		7,3										
174	RR	174BRR1025	615,0	617,5		9,2										
174	RR	174BRR1075	676,3	704,8		8,0										
174	RR	174BRR0715	102,8	108,5		9,0										
174	RR	174BRR0730	121,0	123,2		7,3										
174	RR	174BRR0725	118,0	121,0		9,0										
174	RR	174BRR0990	544,0	553,7		8,3										
174	RR	174BRR0765	163,2	173,4		7,2										
174	RR	174BRR1050	647,6	659,5		8,1										
174	RR	174BRR0975	524,1	531,2		9,5										
174	RR	174BRR0930	449,2	451,8		8,3										
210	RR	210BRR0490	214,5	221,5		10,0										
210	RR	210BRR0445	135,5	148,4		9,0										
210	RR	210BRR0505	237,5	238,6		8,3										
210	RR	210BRR0460	161,8	178,5		9,0										
210	RR	210BRR0485	201,8	214,5		12,0										
210	RR	210BRR0480	198,3	201,8		10,0										
210	RR	210BRR0450	148,4	155,0		9,0										
210	RR	210BRR0470	194,0	195,7		9,0										