

MEMORIAL DESCRITIVO

MODELO: JENROLL EX8

MARCA: JENSEN

ANO DE FABRICAÇÃO 1995

CALANDRA AUTOMÁTICA UTILIZADA PARA PASSADORIA DE LENÇÓIS E FRONHAS COM LARGURA DE 3,3 METROS; COM CAPACIDADE DE 40 METROS POR MINUTO EM TECIDOS DE 100% ALGODÃO E 50 METROS POR MINUTO EM TECIDOS 50% ALGODÃO E 50% POLIÉSTER; CONTENDO 3 ROLOS 800 MM EM LÂMINA DE AÇO PERFURADO REFORÇADOS COM ANÉIS DE SUPORTE; COM CALHAS E EMENDAS ENTRE AS CALHAS FABRICADAS EM AÇO DE QUALIDADE SUPERIOR E RECOZIDAS EM ALTA TEMPERATURA; TUBULAÇÃO DE VAPOR INTEGRADA COM CONEXÕES DE FÁCIL ACESSO NO LADO ESQUERDO DA CALANDRA; CONTROLE AUTOMÁTICO DE EXAUSTÃO EFETUADA COM VENTILADORES INDIVIDUAIS EM CADA ROLO; GRANDE TAXA DE EVAPORAÇÃO DEVIDO A UM FLUXO DE VAPOR TURBULENTO, EM COMBINAÇÃO COM A FABRICAÇÃO DAS CALHAS EM AÇO CARBONO; EQUIPADO COM MOTOR AC COM VARIADOR DE FREQUÊNCIA, QUE PERMITE VARIAR A VELOCIDADE SEGUNDO AS NECESSIDADES; POSSÍVEL DE CONTROLAR A LINHA DE ACABAMENTO INTEIRA DIRETO DO PAINEL DE CONTROLE DO ALIMENTADOR; USANDO TECNOLOGIA QUE EXIGE POUCA MANUTENÇÃO.







Type: JENROLL EX

Volt 415

Hz 50

kW 18

Fabr. Nr. 550202

Phase 3-4

Max Amp 65

Diam. Roll 600 mm.

Width 1500 mm.

STEAM Press 1600 kpa

Air Press 600 kpa

Max Speed 37 m/min



Date 1995 17

JENSEN

JENSEN INDUSTRIES A/S. DK-3700 RØNNE DENMARK

Telephone : +45 56 95 96 53
Telefax : +45 56 95 49 63
Telex : 48140JENSEN DK

This machine has been designed for
paddings with a thickness of

3.5 mm. to 4.5 mm.

The springs are 9 mm. high.

The total diameter of the roller shall
always be 602 mm. to 612 mm.

Accessible STEAM press 900 KPa

type: JENROLL EX
Volt 415
Hz 50
KW 18
CE
Date 1995 17

Fabr. Nr. 350202
Phase 3-4
Max Amp 65

Diam. Roll 600 mm.
Width 1400 mm.
STEAM Press 1600 kpa
Air Press 600 kpa
Max Speed 37 m/min

JENSEN
JENSEN INDUSTRIES A/S DK-3700 RØNNE DENMARK
Telephone: +45 56 95 96 53
Telefax: +45 56 95 49 53
Telex: 48140JENSEN DK

This machine has been designed for
paddings with a thickness of
3.5 mm. to 4.5 mm.
The springs are 9 mm. high.
The total diameter of the roller shall
always be 902 mm. to 912 mm.
Accessible STEAM press 900 KPa