

General / Geral	Model - Modelo	HNTC-180
	Power mode - Combustivel	Diesel
	Driving mode - Modo conducao	Driver/seat
	Max. capacity - Maxima capacidade (kg)	18000
	Load center - Centro de carga (mm)	1200
	Maximum lifting height - Altura maxima de elevacao (mm)	6000
	Load center distance - Distancia do centro de carga (mm)	18000
	Maximum forward reach - Alcance maximo para frente (mm)	3000
	Load capacity at maximum outreach - Capacidade maxima no maior alcance (kg)	6300
	Boom Sections - Secoes da lanca	2
Weight and dimensions / Peso e dimensoes	Lifting Speed with full load - Velocidade de elevacao com carga maxima (m/s)	0.22
	Length to fork face - Comprimento a face do garfo (mm)	5650
	Length with fork - Comprimento com garfo (mm)	8090
	Overall width - Largura total (mm)	2160
	Overall height - Altura total (mm)	2265
	Wheelbase - Entre-eixos (mm)	4000
	Ground clearance - Distancia do chao (mm)	150
	Outside turning radius - Raio de giro externo (mm)	8250
	Overall weight - Peso total (kg)	27000
	Fork size:length*width*thickness - Tamanho garfo: comprimento*largura*espessura (mm)	2440x220x110
Engine / Motor	Manufacturer - Fabricante	DF Cummins
	Emission standard - Padrao de emissao	EU Stage III
	Model - Modelo	QSB6.7-C190
	Displacement / Cylinders - Cilindradas / Cilindros (L)	6.7/6
	Rated Power / speed - Potencia / Velocidade (kW/rpm)	142/2200
	Maximum torque - Torque maximo (N.m/rpm)	930/1300
	Fuel tank - Tanque de combustivel (L)	300
Transmission / Transmissao	Battery - Bateria (V)	24
	Manufacturer - Fabricante	ZF
	Transmission type - Tipo de transmissao	Torque converter with automatic power shift
	Shifting - Mudanca de marcha	Automatic power shift
	Number of gears (forward / reverse) - Numero de marchas (para frente / para tras)	03/03
	Maximum Travelling speed - Velocidade de deslocamento maxima (km/h)	20
	Parking brake - Freio de estacionamento	Spring powered disc
Hydraulic / Hidraulico	Service brake - Freio	Hydraulic caliper disc
	Hydraulic pump type - Bomba hidraulica	-
	Hydraulic flow / Pressure - Fluxo hidraulico / Pressao (L/min-Mpa)	260-23
Wheels, etc / Rodas, etc	Hydraulic Oil - Oleo hidraulico	300
	Front - Dianteira	4x12.00-20 Driving
	Rear - Traseira	2x12.00-20 Steering
	Safety cab homologation - Homologacao de cabine de seguranca	ROPS/FOPS
	Air-conditioning system - Sistema de ar-condicionado	Cooling/heating
	Controls - Controles	Electronic joystick



## DOUBLE ARM TELEHANDLER

### HNTC-180

The HNTC-180 double-arm telescopic forklift has a rated lifting capacity of 18 tons, a maximum extension distance of 2.5 meters, a maximum lifting height of 6 meters, and the following specifications:







FUJIAN SOUTHCHINA HEAVY MACHINERY MANUFACTURE CO., LTD